

半自动真空塞孔机

Semi-automatic vacuum plug hole machine

可订做其他规格
Can be custom-made



产品用途 Usage

- 双面板油墨塞孔
Double sided board ink plug hole
- 高频板树脂塞孔
High frequency board resin plug hole

产品特点

- 自带真空系统塞孔段, 适用高粘度树脂塞孔, 实现水平式选择性以及整板塞孔, 避免返工, 降低报废率。
- 配套进口超高真空系统, 真空度可达50Pa, 彻底解决丝印时气泡所产生的不良问题。
- 机械设置自锁功能, 保证塞孔的稳定性和平衡性, 还有操作人员的安全性。
- 四柱式动力升降系统, 机械强度高, 刚性度好, 设备稳定性强, 有效延长使用年限。

Features

- Equipped with a vacuum system plug hole section, suitable for high viscosity resin plug holes, achieving horizontal selectivity and whole plate plug holes, avoiding rework and reducing scrap rate.
- Equipped with an imported ultra-high vacuum system, the vacuum degree can reach 50Pa, completely solving the problem of bubbles generated during screen printing.
- The mechanical setting has a self-locking function to ensure the stability and balance of the plug hole, as well as the safety of the operator.
- Robot loading and unloading, online operation of the entire line, achieving fully intelligent and automated production, saving at least 5-7 of labor costs.
- The four column power lifting system has high mechanical strength, good rigidity, strong equipment stability, and effectively extends its service life.

技术参数 Technical Parameters	
最大印刷面积 Max.Printing Area (Y*X)	730mm*630mm
最小印刷面积 Min.Printing Area (Y*X)	400mm*350mm
最大塞孔网板尺寸 Max.Frame Size (Y*X)	1200*1200mm
最小塞孔网板尺寸 Min.Frame Size (Y*X)	900mm*900mm
印刷厚度 Printing Thickness	0.4mm-8.0mm
机械性能 Mechanical Speed	2-3.5PNL/min R≤8:1
CCD对位精度 CCD Alignment Accuracy	±0.005mm
真空度 Vacuum degree	50Pa
使用工作气压 Operating Air Pressure	0.3-0.7Mpa
设备功率 Power	380V 50Hz 15KW
外观尺寸 Machine Dimension (L*W*H)	3450*3200*2100mm
工作台面积 Work Table Size (Y*X)	1000*1050mm

智能自动化真空塞孔机

Intelligent automatic vacuum plug hole machine

可订做其他规格
Can be custom-made



产品用途 Usage

- 双面板油墨塞孔
Double sided board ink plug hole
- 高频板树脂塞孔
High frequency board resin plug hole

产品特点

- 自带真空系统塞孔段, 适用高粘度树脂塞孔, 实现水平式选择性以及整板塞孔, 避免返工, 降低报废率。
- 配套进口超高真空系统, 真空度可达50Pa, 彻底解决丝印时气泡所产生的不良问题。
- 机械设置自锁功能, 保证塞孔的稳定性和平衡性, 还有操作人员的安全性。
- 四柱式动力升降系统, 机械强度高, 刚性度好, 设备稳定性强, 有效延长使用年限。

Features

- Equipped with a vacuum system plug hole section, suitable for high viscosity resin plug holes, achieving horizontal selectivity and whole plate plug holes, avoiding rework and reducing scrap rate.
- Equipped with an imported ultra-high vacuum system, the vacuum degree can reach 50Pa, completely solving the problem of bubbles generated during screen printing.
- The mechanical setting has a self-locking function to ensure the stability and balance of the plug hole, as well as the safety of the operator.
- Robot loading and unloading, online operation of the entire line, achieving fully intelligent and automated production, saving at least 5-7 of labor costs.
- The four column power lifting system has high mechanical strength, good rigidity, strong equipment stability, and effectively extends its service life.

技术参数 Technical Parameters	
最大印刷面积 Max.Printing Area (Y*X)	730mm*630mm
最小印刷面积 Min.Printing Area (Y*X)	400mm*350mm
最大塞孔网板尺寸 Max.Frame Size (Y*X)	1200*1200mm
最小塞孔网板尺寸 Min.Frame Size (Y*X)	900mm*900mm
印刷厚度 Printing Thickness	0.4mm-8.0mm
机械性能 Mechanical Speed	3-4PNL/min R≤8:1
CCD对位精度 CCD Alignment Accuracy	±0.005mm
真空度 Vacuum degree	50Pa
使用工作气压 Operating Air Pressure	0.3-0.7Mpa
设备功率 Power	380V 50Hz 15KW
外观尺寸 Machine Dimension (L*W*H)	6200*1800*2100mm
工作台面积 Work Table Size (Y*X)	1000*1050mm