



防水型 圆形连接器

弯角公插头
WF系列 威浦品牌

系列	类型	接插方式	材质			防护等级
			外壳	绝缘体	接触体	
YEDWF系列	弯角公插头	螺纹连接	锌铝合金 (镀铬)	热塑塑料PPS (耐高温260°C)	铜 (镀金)	IP65




插座与面板 配合直径	16	20	24	28
H	60	80	80	93
L	45.5	53	56.3	70
Ød	7~8	8~10.5	8~10.5	11.5~13.6


单位: mm

孔位排列图(从针的方向看)


YEDWF16系列





YEDWF20系列



YEDWF24系列



YEDWF28系列



代码	插座与面板 配合直径	芯数	接插件种类	接线方式	出线方式	适配插孔类型						
						直通母插头	面板安装方型母插座	面板安装螺母型母插座				
YEDWF16J2TV	16	2	插针	焊接	电缆护套	YEDWF16K2ZIB	YEDWF16K2Z	YEDWF16K2ZM				
YEDWF16J3TV		3				YEDWF16K3ZIB	YEDWF16K3Z	YEDWF16K3ZM				
YEDWF16J4TV		4				YEDWF16K4ZIB	YEDWF16K4Z	YEDWF16K4ZM				
YEDWF16J5TV		5				YEDWF16K5ZIB	YEDWF16K5Z	YEDWF16K5ZM				
YEDWF16J7TV		7				YEDWF16K7ZIB	YEDWF16K7Z	YEDWF16K7ZM				
YEDWF16J9TV		9				YEDWF16K9ZIB	YEDWF16K9Z	YEDWF16K9ZM				
YEDWF16J10TV		10				YEDWF16K10ZIB	YEDWF16K10Z	YEDWF16K10ZM				
YEDWF20J2TV		20				2	插针	焊接	电缆护套	YEDWF20K2ZIB	YEDWF20K2Z	YEDWF20K2ZM
YEDWF20J3TV						3				YEDWF20K3ZIB	YEDWF20K3Z	YEDWF20K3ZM
YEDWF20J4TV						4				YEDWF20K4ZIB	YEDWF20K4Z	YEDWF20K4ZM
YEDWF20J5TV	5		YEDWF20K5ZIB	YEDWF20K5Z	YEDWF20K5ZM							
YEDWF20J7TV	7		YEDWF20K7ZIB	YEDWF20K7Z	YEDWF20K7ZM							
YEDWF20J9TV	9		YEDWF20K9ZIB	YEDWF20K9Z	YEDWF20K9ZM							
YEDWF20J12TV	12		YEDWF20K12ZIB	YEDWF20K12Z	YEDWF20K12ZM							
YEDWF24J2TV	24		2	插针	焊接	电缆护套				YEDWF24K2ZIB	YEDWF24K2Z	YEDWF24K2ZM
YEDWF24J3TV			3							YEDWF24K3ZIB	YEDWF24K3Z	YEDWF24K3ZM
YEDWF24J4TV			4							YEDWF24K4ZIB	YEDWF24K4Z	YEDWF24K4ZM
YEDWF24J9TV		9	YEDWF24K9ZIB				YEDWF24K9Z	YEDWF24K9ZM				
YEDWF24J10TV		10	YEDWF24K10ZIB				YEDWF24K10Z	YEDWF24K10ZM				
YEDWF24J12TV		12	YEDWF24K12ZIB				YEDWF24K12Z	YEDWF24K12ZM				
YEDWF24J19TV		19	YEDWF24K19ZIB				YEDWF24K19Z	YEDWF24K19ZM				
YEDWF28J3TV		28	3				插针	焊接	电缆护套	YEDWF28K3ZIB	YEDWF28K3Z	YEDWF28K3ZM
YEDWF28J4TV			4							YEDWF28K4ZIB	YEDWF28K4Z	YEDWF28K4ZM
YEDWF28J7TV			7							YEDWF28K7ZIB	YEDWF28K7Z	YEDWF28K7ZM
YEDWF28J8TV	8		YEDWF28K8ZIB	YEDWF28K8Z	YEDWF28K8ZM							
YEDWF28J10TV	10		YEDWF28K10ZIB	YEDWF28K10Z	YEDWF28K10ZM							
YEDWF28J12TV	12		YEDWF28K12ZIB	YEDWF28K12Z	YEDWF28K12ZM							
YEDWF28J16TV	16		YEDWF28K16ZIB	YEDWF28K16Z	YEDWF28K16ZM							
YEDWF28J20TV	20		YEDWF28K20ZIB	YEDWF28K20Z	YEDWF28K20ZM							
YEDWF28J24TV	24		YEDWF28K24ZIB	YEDWF28K24Z	YEDWF28K24ZM							
YEDWF28J26TV	26		YEDWF28K26ZIB	YEDWF28K26Z	YEDWF28K26ZM							

电气技术特性

YEDWF16系列

芯数	2	3	4	5	7	9	10
额定电流(A)	10						
接触件直径	Ø1.5x2	Ø1.5x3	Ø1x4	Ø1x5	Ø1x7	Ø1x9	Ø1x10
工作电压(V)	500			400			
耐压(V)	1500			1200			
接触电阻(mΩ)	2.5			5			
线规(mm²/AWG)	≤2/14			≤0.75/18			

YEDWF20系列

芯数	2	3	4	5	7	9	12		
额定电流(A)	25							10	5
接触件直径	Ø2.5x2	Ø2.5x3	Ø2.5x4	Ø1.5x5	Ø1.5x7	Ø1x9	Ø1x12		
工作电压(V)	500			400					
耐压(V)	1500			1200					
接触电阻(mΩ)	1			2.5		5			
线规(mm²/AWG)	≤4/11			≤2/14		≤0.75/18			

YEDWF24系列

芯数	2	3	4	9	10	12	19			
额定电流(A)	25							5.25	10	5
接触件直径	Ø2.5x2	Ø2.5x3	Ø2.5x4	Ø1.5x9	Ø1.5x10	Ø1.5x12	Ø1x19			
工作电压(V)	500			400						
耐压(V)	1500			1200						
接触电阻(mΩ)	1			5.1		2.5		5		
线规(mm²/AWG)	≤4/11			≤0.75/18		≤4/11		≤0.75/18		

YEDWF28系列

芯数	3	4	7	8	10	12	16	20	24	26
额定电流(A)	50									
接触件直径	Ø3.5x3	Ø2.5x4	Ø2.5x7	Ø2.5x8	Ø2.5x10	Ø1.5x12	Ø1.5x16	Ø1x20	Ø1x24	Ø1x26
工作电压(V)	500									
耐压(V)	1500									
接触电阻(mΩ)	0.5			1			2.5		5	
线规(mm²/AWG)	≤10/7			≤4/11			≤2/14		≤0.75/18	

技术参数

接插方式	螺纹连接
接线方式	焊接: Ø1, Ø2.5, Ø3.5, Ø5.5
接插次数	500
温度范围	-40°C ~ +85°C
绝缘电阻	2000MΩ



代码
YEDWF16J2TV
YEDWF16J3TV
YEDWF16J2TV

